

Read Me First!




Engineering the flow of communication™

1 Elmcroft Road
Stamford, Connecticut 06926-0700
www.pitneybowes.com



DM300c Digital Mailing System

For Service or Supplies



Customer Support: 1.800.522.0020
Product Name: DM300c
Model Number: 3C00
AW21912 Rev A 11/08

© 2008 Pitney Bowes Inc.
All Rights Reserved
Printed in the USA

 Printed on recyclable paper




* A W 2 1 9 1 2 R E V A *




Self Install Guide
US English Version

Contents


DM300c
Mailing System




MP9G
Weighing Platform
(Optional)



Stacker




Moistener
(Optional)




Ink cartridge
(Reorder #765-9)



Print Head



Analog Phone Cord




Power Cord




Tape Strips



Operator Guide



Self Install Guide




Quick Reference Guide






Please do not apply power until Step 3.


Step 1 Remove All Shipping Tapes and Packing Material



1a Open ink access cover and remove tape and shipping material. Then close ink cartridge guard followed by ink access cover.



1b Remove shipping foam and tapes.



1c Close printer deck by lifting it and rotating clearance lever counterclockwise.

Step 2 Connect Analog Phone Cord




What is an analog phone line?

The following are usually analog phone lines:

- Fax lines
- Lines used by modems or credit card readers
- Residential phone lines

If you are unsure about your phone line, contact your telephone company or local network administrator.





analog phone cord

Scale codes for locations in Alaska and California



Locations near a boundary may enter either code.



Step 5 Set Time

Key in time with hours first and then minutes.

1 2 3
4 5 6
7 8 9
Back
C

Set Time
Current: XX:XX PM
Enter Time
(HH:MM)
◀ Select AM/PM

Select **Select AM/PM**.

Select AM/PM

◀ AM

◀ PM

Select **AM** or **PM**.

Confirm Time

Proceed with time set to X:XX PM?

◀ Yes

◀ No


Select **Yes** to confirm time.

Step 6 Install the Print Head and Ink Cartridge

Install Ink Tank/
Print Head
Open Cover to start
replacement.


First install the print head.

6a Open the ink access cover.



6b Remove the print head from packaging and remove tape strip.

6c Flip open the ink cartridge guard.



6d Slide the print head pegs down into the grooves.

6e Squeeze the tabs on the sides of the print head and push the print head flush against the wall.

Scale codes for locations in the United States



Locations near a boundary may enter either code.

State	Code	State	Code
Missouri		Oregon	
North of Springfield	15	Salem and north	18
Springfield and south	14	South of Salem	17
Montana		Pennsylvania	16
Helena and north	18	Rhode Island	16
South of Helena	17	South Carolina	13
Nebraska	16	South Dakota	17
Nevada	13	Tennessee	13
New Hampshire	17	Texas	
New Jersey	16	NE of Colorado River	12
New Mexico	11	SE of Colorado River	11
New York		Utah	13
Kingston and north	17	Vermont	17
South of Kingston	16	Virginia	
North Carolina		North of Roanoke	15
Raleigh and north	14	Roanoke and south	14
South of Raleigh	13	Washington DC	15
North Dakota	18	Washington State	18
Ohio		West Virginia	15
Akron and north	16	Wisconsin	
South of Akron	15	Green Bay and north	18
Oklahoma		South of Green Bay	17
North of Oklahoma City	14	Wyoming	15
Oklahoma City and south	13		

Scale codes for locations in the United States




Locations near a boundary may enter either code.


State	Code	State	Code
Alabama		Illinois	
Birmingham and north	13	North of Springfield	16
South of Birmingham	12	Springfield and south	15
Alaska (see map on pg 20)		Indiana	
Arizona		North of Indianapolis	16
Phoenix and north	12	Indianapolis and south	15
South of Phoenix	11	Iowa	
Arkansas	13	North of Des Moines	17
California (see map on pg 20)		Des Moines and south	16
Colorado		Kansas	
Denver and north	13	North of Wichita	15
South of Denver	12	Wichita and south	14
Connecticut	16	Kentucky	14
Delaware	15	Louisiana	12
Florida		Maine	18
W Palm Beach and north	11	Maryland	15
South of W Palm Beach	10	Massachusetts	17
Georgia	12	Michigan	
Hawaii	9	NW of Lake Michigan	18
Idaho		SE of Lake Michigan	17
N of Salmon River Mtns.	17	Minnesota	18
S of Salmon River Mtns.	16	Mississippi	
		Kosciusko and north	13
		South of Kosciusko	12

Step 6 Install the Print Head and Ink Cartridge


Now install the ink cartridge.




6f Remove the ink cartridge from the bag and make sure the tape strip is peeled off.



6g Lower the tank into the cavity. The ridges on either side of the tank will slide into the grooves.





6h Return the guard back to the operating position and click to close.



6i Close the ink access cover. The system will automatically perform printer maintenance.


Step 7 Test Print

If you want a test print, follow these steps.




For proper printing, position mail flat against rear registration wall and gently slide mail to the right on printer deck.

OR




Load tape into tape feeder and press **Tape** button.



If the test print is good, select **Yes**.

Good test print - no missing lines



If the test print is poor, select **No** to perform additional maintenance.

Poor test print - missing lines

Troubleshooting

Print Head or Ink Cartridge Fault

Try installing print head or ink cartridge again as described in Step 6. If problem persists, call Pitney Bowes.

Mail Skewed

Clear message and try inserting envelope with it aligned flat against the rear registration wall.

No Dial Tone

Check that you are using an analog line such as

- most fax machine lines;
- lines used by computer modem or credit card reader;
- residential phone lines.

Check that you have entered a dialing prefix if your phone system needs a code to reach an outside line.

If you are using a DSL line you should use a DSL filter obtained from your DSL provider.

Cannot Reach Data Center

Check that you have entered a dialing prefix if your phone system needs a code to reach an outside line.

Not Enough Funds

You have tried to add more postage than you have in your account at Pitney Bowes. Refill a smaller amount and try again.

To Change Information During the Setup Procedure

- Press **Back/C** key on numeric keypad.
- At **Install Not Complete**, either go back to the previous step or return to the Install Start.

To Change Information After the Setup Program is Complete

- Press **Menu**.
- Press Down button to scroll and select **Advanced Features**.
- Select **Run Install Mode**.


For Customer Support

- Dial 1-800-522-0020





Position Stacker


Position the stacker next to the DM300c as shown. The stacker provides a convenient location to store your metered mail, tape sheets, and operator guide.



Step 8 Install Weighing Platform (optional)



OR



If you have purchased an external USB weighing platform, connect it to the back of the DM300c using the USB cable supplied.


Step 9 Scale Location Code

If you have installed your weighing platform, key in the correct scale code for your geographical location.

Note: To clear the default value or re-enter the code, press the **Back/C** key to clear.



Codes can be found in the back of this guide.



Select **Accept**.

Step 10 Setup Dialing Prefix

Some phones require that you dial a prefix before dialing an outside number.





If your phone requires a dialing prefix, enter the prefix and select **Accept**.


If no prefix is required, select **No Prefix Required**.

Install Moistener (optional)

If you have purchased the optional moistener with your DM300c, position the moistener on the left side of the printer deck as shown. Slide moistener from left to right aligned with the top of the printer deck.




The moistener will click into place.



Fill the moistener reservoir with Pitney Bowes E-Z Seal® Sealing Solution. You may fill it later if you don't plan on moistening and sealing envelopes right now.

Step 13 Congratulations! Your Mailing System is Ready to Use



Select **OK**.

To customize your postage settings and learn all about using your DM300c, see the Operator Guide.




If you are unable to complete this step, call Customer Support at 1-800-522-0020.

Step 11 Refill Postage

Your DM300c system will automatically dial the Pitney Bowes Data Center and after a brief pause, display your Postage By Phone™ balance.




You have to transfer postage funds from your Postage by Phone account to your system before you can use it. To do this, select **Refill Postage**.





Select **Accept**, or press Back/C and key in the amount you wish to transfer. You can enter whole dollar amounts only.

Continue to set up moistener and stacker. ➡

Step 11 Refill Postage (continued)




Select **Yes** to confirm amount.



To print a receipt, select **Print Receipt** and follow prompt or select **Continue**.


Step 12 Check for System Updates (optional)

If there are downloads available, you will see the following screen.



Select **Download Now**.

You will now observe the downloading of updates. When the downloading is complete you will see the following screen.



Select **Continue**.



Depending on the software that is downloaded, your system may automatically restart.